




Pin description

Pin	Name	I/O type	Function
1	OE	Input	Output enable
			High: Specified frequency output from OUT pin Low: Out pin is low (weak pull down), only output driver is disabled.
	\overline{ST}	Input	Standby
			High: Specified frequency output from OUT pin Low: Out pin is low (weak pull down), Device goes to standby mode. Supply current reduces to the least as I_{std} .
2	GND	Power	Ground
3	OUT	Output	Clock output
4	V _{CC}	Power	Power supply


External dimensions

(Unit: mm)


SG-9101CG




SG-9101CG




SG-9101CE




SG-9101CE




SG-9101CB




SG-9101CB



SG-9101CA



SG-9101CA





■Notes:

In order to achieve optimum jitter performance, the 0.1 μ F capacitor between V_{CC} and GND should be placed. It is also recommended that the capacitors are placed on the device side of the PCB, as close to the device as possible and connected together with short wiring pattern.




Specification Graph (Typical supplemental specification. Unless otherwise specified $T_{\text{use}} = 25^{\circ}\text{C}$, $L_{\text{CMOS}} = 15\text{pF}$)


Current Consumption



Output disable current



Standby current






■ Notes:

Spread percentage : $\pm 2.0\%$, Modulation frequency : 25.4 kHz , Modulation profile : Hershey-kiss

Specification Graph (Typical supplemental specification. Unless otherwise specified $T_{\text{use}} = 25^{\circ}\text{C}$, $L_{\text{CMOS}} = 15\text{pF}$)

Cycle-to-Cycle Jitter Peak-Peak



■ Notes:


Spread percentage : $\pm 2.0\%$, Modulation frequency : 25.4 kHz , Modulation profile : Hershey-kiss




Spread Spectrum Specification Graph

Spread Spectrum Profile f_0 : 170 MHz / Spread spectrum : ± 2.0 % / Modulation frequency : 25.4 kHz


Hershey-kiss



Sine-wave





Triangle




Harmonics Specification Graph

(Typical supplemental specification. Unless otherwise specified $T_{use} = 25^\circ\text{C}$, $L_{CMOS} = 15\text{pF}$, $V_{cc} = 3.3\text{V}$)Harmonics spectrum ($f_0 = 20\text{ MHz}$)


No spread spectrum

Center spread ± 2.0 % , Hershey-kiss , 25.4 kHz


Modulation profile




Modulation frequency



Spread percentage



Output frequency







Notes:

Harmonics order attenuation is normalizing to no-spread spectrum mode.


Specification Graph (Typical supplemental specification. Unless otherwise specified $T_{use} = 25^{\circ}\text{C}$, $L_{CMOS} = 15\text{pF}$)

Rise/Fall Time ($f_o = 20\text{ MHz}$)




Harmonics comparison


Center spread $\pm 2.0\%$, Hershey-kiss, 25.4 kHz



Normalize to $V_{cc} = 3.3\text{V}$.



Normalize to $V_{cc} = 3.3\text{V}$.



Normalize to Rise/Fall time = "Fast".

■ Notes:

frequency	slow	default	fast
0.67 M – 20 M	See Slow	See Default	See Fast
20 M – 40 M	-	See Default	See Fast
40 M – 170 M	-	See Fast	See Fast



Simulation Model

- IBIS Model is available upon request. Please contact us.
Information Required: Oscillator operating condition (i.e. Power Supply, Rise/Fall Time, Temperature)

ESD Rating


Test items	Breakdown voltage
Human Body Model (HBM)	2000V
Machine Model (MM)	250V
Charged Device Model (CDM)	750V

Device Material & Environmental Information

Model	Package Dimensions	# of Pins	Reference Weight (Typ.)	Terminal Material	Terminal Plating	Complies With EU RoHS	Pb Free	MSL Rating	Peak Temp. (Max)
SG-9101CG	2.5x2.0x0.7mm	4	13 mg	W	Au	Yes	Yes	1	260°C
SG-9101CE	3.2x2.5x1.0mm	4	25 mg	W	Au	Yes	Yes	1	260°C
SG-9101CB	5.0x3.2x1.1mm	4	51 mg	W	Au	Yes	Yes	1	260°C
SG-9101CA	7.0x5.0x1.3mm	4	143 mg	W	Au	Yes	Yes	1	260°C

SMD products Reflow profile(example)

The availability of the heat resistance for reflow conditions of JEDEC-STD-020D.01 is judged individually. Please inquire.



	<ul style="list-style-type: none"> Pb free.
	<ul style="list-style-type: none"> Complies with EU RoHS directive. <ul style="list-style-type: none"> About the products without the Pb-free mark. Contains Pb in products exempted by EU RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.)




Device Marking

Model	Factory Programmed Part Marking	Field Programmable Part Marking (Blank Samples)
SG-9101CG	<p>Frequency: 170.S1 Product code: S1 Lot No.: A23DK 1pin mark</p>	<p>Product code: S1 Lot No.: A23DK 1pin mark</p>
SG-9101CE	<p>Frequency: 170.0S1 Product code: S1 Lot No.: A23DK 1pin mark</p>	<p>Product code: S1 Lot No.: A23DK 1pin mark</p>
SG-9101CB	<p>Frequency: 170.0S1 Product code: S1 Lot No.: A23DK 1pin mark</p>	<p>Product code: S1 Lot No.: A23DK 1pin mark</p>
SG-9101CA	<p>Frequency: 170.00S1 Product code: S1 Lot No.: A23DK 1pin mark</p>	<p>Product code: S1 Lot No.: A23DK 1pin mark</p>

Standard Packing Specification

SMD products are packed in the shipping carton as below table in accordance with taping standards EIA-481 and IEC-60286



Standard Packing Quantity & Dimension(Unit mm)

Model	Quantity (pcs/Reel)	Reel Dimension			Career Tape Dimension				Direction of Feed (L= Left Direction)
		a	b	W	A	B	C	D	
SG-9101CG	3000	Φ180	Φ60	9	4	5.25	8	1.15	L
SG-9101CE	2000	Φ180	Φ60	9	4	5.25	8	1.4	L
SG-9101CB	1000	Φ180	Φ60	13	8	7.25	12	1.4	L
SG-9101CA	1000	Φ254	Φ100	17.5	8	9.25	16	2.3	L

PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Seiko Epson, all environmental initiatives operate under the Plan-Do-Check-Action (PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard.

All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification.

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone layer, and global deforestation.





WORKING FOR HIGH QUALITY

In order provide high quality and reliable products and services than meet customer needs,

Seiko Epson made early efforts towards obtaining ISO9000 series certification and has acquired ISO9001 for all business establishments in Japan and abroad. We have also acquired ISO/TS 16949 certification that is requested strongly by major automotive manufacturers as standard.

ISO/TS16949 is the international standard that added the sector-specific supplemental requirements for automotive industry based on ISO9001.

► Explanation of the mark that are using it for the catalog

	► Pb free.
	► Complies with EU RoHS directive. *About the products without the Pb-free mark. Contains Pb in products exempted by EU RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.)
	► Designed for automotive applications such as Car Multimedia, Body Electronics, Remote Keyless Entry etc.
	► Designed for automotive applications related to driving safety (Engine Control Unit, Air Bag, ESC etc).

Notice

- This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Seiko Epson.
- The information about applied data, circuitry, software, usage, etc. written in this material is intended for reference only. Seiko Epson does not assume any liability for the occurrence of customer damage or infringing on any patent or copyright of a third party. This material does not authorize the licensing for any patent or intellectual copyrights.
- When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Seiko Epson in advance.
 - / Space equipment (artificial satellites, rockets, etc.) / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.) / Medical instruments to sustain life / Submarine transmitters / Power stations and related / Fire work equipment and security equipment / traffic control equipment / and others requiring equivalent reliability.
- All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective.